



UNIFORMLY DISTRIBUTED LOAD

MESH TYPE mm x mm	THICKNESS mm		DISTANCE BETWEEN SUPPORTS							
			400 mm	500 mm	600 mm	800 mm	1000 mm	1200 mm	1400 mm	1500 mm
100 x 25	25	U	5370	2770	1600	680	350	200	130	100
		d	4	5	6	8	10	12	14	15
40 x 40	25	U	3420	1760	1020	430	220	130	80	70
		d	4	5	6	8	10	12	14	15
40 x 40	30	U	6210	3200	1860	790	400	230	150	120
		d	4	5	6	8	10	12	14	15
8 x 8	30	U	7660	3960	2310	980	500	290	180	150
		d	4	5	6	8	10	12	14	15
19 x 19	30	U	6490	3360	1950	830	430	250	160	130
		d	4	5	6	8	10	12	14	15
40 x 40	38	U	12090	6260	3650	1550	790	460	290	240
		d	4	5	6	8	10	12	14	15
19 x 19	40	U	14390	7490	4370	1860	960	560	350	280
		d	4	5	6	8	10	12	14	15
50 x 50	50	U	22220	11600	6780	2890	1490	860	540	440
		d	4	5	6	8	10	12	14	15
19 x 19	50	U	28830	15140	8880	3800	1960	1140	720	580
		d	4	5	6	8	10	12	14	15
25 x 50	55	U	39790	20960	12320	5280	2720	1580	1000	810
		d	4	5	6	8	10	12	14	15
38 x 38	63	U	85090	44880	26410	11330	5850	3400	2150	1750
		d	4	5	6	8	10	12	14	15



U = Uniformly Distributed Load kg/m²

d = Deflection of corresponding load (expressed in mm)

The load values refer to a L/100 (1%) deflection

The load values indicated represent average values (tolerance +/- 15%)